




Adapter
N Female to 3.5mm Female

CACTechnology

ANAF35F00

DATA SHEET



Electrical Data	Materials	Enviromental Data	Mechanical Data
Impedance :50 ohm	Housing: Stainless Steel; Passivating	Salt Spray Test:48h	Mating Cycles:2000
Frequency:DC-18GHz	Contact female:BeCu; Gold Plated 1.27u	Vibration:MIL-STD 202 214A	Coupling Proof Torque: 1.69N.m
VSWR:1.15Max 18GHz	Contact male:Brass; Gold Plated 1.27u	Thermal shaoock:MIL-STD 202 107G	Coupling Nut Retention: 445N min
IL:0.06sq(f_GHz)	Center Capture: PTFE	Weight:31g	Center Contact Captivation(Axial): 66.7N min
Dielectric Withstanding Voltage:1500V	Nut:Brass; Gold Plated 1.27u	Temp:-55 - +125	Force to Engagement:0.68N.m
Insulation Resistance: 5000Mohm	Clasp:QSn6.5-0.1 (Bronze)	2011/65/EU (RoHS): compliant	Force to Disengagement:N/A

proprietary information: the information with this data sheet is
proprietary and shall not be used for disclosed without prior written
permission from CAC Technology .

Date:	2012.10.29	www.cactechnology.com Tel: 0086-551-63718423 Fax: 0086-551-63718413 Email: sales@cactechnology.com Add: Chuangzhi Square, No. 429, Maanshan South Rd. Hefei, Anhui, China (230051)
Drawn:	Yuan Jin	
Check:	Zhen Wang	
Appr:	Rugang Hu	